



Pallet truck/Standard



Integral-type pump

- 1.High reliability, suitable for variety of environments.It can be used for 3-5 years under normal maintenance
- 2.The first design of forging & casting integral pump, which prevents any loosening and leakage.
- 3.High-strength alloy steel carefully rafted, increased loading capacity
- 4.Set the active safety valve to prevent over loading of operation
- 5.Option: rubber wheel,Polyurethane wheel
double(Nylon,polyurethane) wheel

Model		CBY20-II	CBY25-II	CBY30-II
Load capacity	kg	2000	2500	3000
Lift height	mm	190/200		
Min. Height	mm	75/85		
Outside fork spread	mm	520/550/685		
Fork length	mm	800/900/1000/1100/1150/1220		
Overall length	mm	1230/1330/1430/1530/1580/1650		
Steering Wheel	mm	Φ180×50/Φ200×50		
Load wheel	mm	Φ80×70/Φ80×74		
Turning radius	mm	1250		
Standard wheel		single Nylon wheel		
Package		6units packed one wooden pallet		



Welding pump,with leaking proof design

- 1.With overloading safety valve
- 2.Chrome plate piston
- 3.Option: rubber wheel,Polyurethane wheel
double(Nylon,polyurethane) wheel

Model		CBY20-III	CBY25-III	CBY30-III
Load capacity	kg	2000	2500	3000
Lift height	mm	190/200		
Min. Height	mm	75/85		
Outside fork spread	mm	520/550/685		
Fork length	mm	800/900/1000/1100/1150/1220		
Overall length	mm	1230/1330/1430/1530/1580/1650		
Steering Wheel	mm	Φ180×50/Φ200×50		
Load wheel	mm	Φ80×70/Φ80×74		
Turning radius	mm	1250		
Standard wheel		single Nylon wheel		
Package		6units packed one wooden pallet		



Pallet truck/Special

Pallet Truck Quick Lift

- 1.the fork could be raised to the Maximum Height in 5 times of handle operation.
- 2.The integral-type pump body contains hydraulic circuit and hydraulic oil tank,which ensures the entire hydraulic system completely sealed and solves the common problem of oil leaking
- 3. Professional designed quick lift hydraulic system, it can reach the highest volumetric efficiency.



Model		EP20Q	EP25Q
Load capacity	kg	2000	2500
Lift height	mm	190/200	
Min. Height	mm	75/85	
Outside fork spread	mm	520/550/685	
Fork length	mm	800/900/1100/1150/1220	
Overall length	mm	1230/1330/1430/1530/1580/1650	
Steering Wheel	mm	Φ180×50/Φ200×50 nylon/polyurethane/rubber	
Load wheel	mm	Φ80×70/Φ74×70 single/tandem nylon(polyurethane)	
Turning radius	mm	1250	
Package		6units packed one wooden pallet	

Low profile pallet truck

Option: polyurethane wheel, double(Nylon,polyurethane)wheel



Model		EP10L	EP15L	EP20L
Load capacity	kg	1000	1500	2000
Lift height	mm	85	135	135
Min. Height	mm	35	51	51
Outside fork spread	mm	520/685		540/685
Fork length	mm	1150/1220		1150/1220
Overall length	mm	1430/1530		1547/1617
Steering Wheel	mm	Φ140×54	Φ180×50	Φ150
Load wheel	mm	Φ34×58	Φ51×60	Φ58
Turning radius	mm	1250		
Standard wheel		single Nylon wheel		
Package		6units packed one wooden pallet		